



- 

Built-in Anamorphic
De-squeeze
- 

Frame Grab &
Overlay
- 

99.9%
Rec.709
- 

170°
Viewing
Angle
- 

CNC-Machined
Aerospace Aluminum
- 

2000 Nit
Ultra-Bright
- 

10W
Low Power
Consumption



- 

5.5" 1200 Nit
Brightness
- 

Fanless Design
- 

Camera Control
- 

Custom 3D LUT
- 

Robust Metal
Housing
- 

4K HDMI Output



- 

7" 1200 Nit
Brightness
- 

Fanless Design
- 

Camera Control
- 

Custom 3D LUT
- 

Robust Metal
Housing
- 

4K HDMI Output



What's in the Box



GM6S Pro Kit1

- | | | | |
|----------------|----|-----------------|----|
| Monitor | ×1 | Cold Shoe Mount | ×1 |
| Dustless Cloth | ×1 | Crowbar | ×1 |
| Hood | ×1 | | |



GM6S Pro Kit2

- | | | | |
|-----------------|----|-------------------------------------|----|
| Monitor | ×1 | Standard HDMI to Mini Cable | ×1 |
| Crowbar | ×1 | Standard HDMI to Standard HDMICable | ×1 |
| Hood | ×1 | Dustless Cloth | ×1 |
| Cold Shoe Mount | ×1 | Standard HDMI to Micro Cable | ×1 |

Tech Specs

Model	GM6S Pro
Screen	5.5" IPS HD Ultra-Bright Touch Screen
Screen Ratio	16:9
Resolution	1920×1080
Contrast Ratio	1200:1
Color Depth	8bit
Visual Angle	170°H/170°V
Brightness	2000nit+10%
Input Power	Max. 10W
Power Supply	DC Input: 7-24V, Φ5.5mm×2.1 Plug DC Output: 7.8+0.3V/1.5A, Φ5.5mm×2.1 Plug USB-C: 9V 2A(USB PD) NP-F Battery: 7.2V F550/F750/F970 Lithium Battery
Material	Metal
Video Format	480i & 576i@50/60Hz 480P & 576P@50/60Hz 1280×720P@50/60Hz 1920×1080i@50/60Hz 1920×1080P@23.98/24/25/29.97/30/50/59.94/60Hz 3840×2160P@23.98/24/25/29.97/30/50/59.94/60Hz 4096×2160P@23.98/24/25/29.97/30/50/59.94/60Hz
Audio Output	3.5mm Earphone Dual-Channel Output Support LUT Lead-in and Firmware Upgrade with SD Card
SD Card Slot	Support 17/32/33/64/65 Cube Files
Working Temperature	-10~40°C
Dimension	14.5×8.7×2.7cm
Net Weight	286g

What's in the Box



- | | | | |
|-----------------|----|---------------|----|
| Monitor | ×1 | HDMI to Mini | ×1 |
| Hood | ×1 | HDMI to Micro | ×1 |
| Cold Shoe Mount | ×1 | HDMI to HDMI | ×1 |

Optional Purchase



- | | | | |
|-------------------------|----|-------------------|----|
| GMC-S2 Multi | ×1 | GMC-U5 Mini USB | ×1 |
| GMC-U4 Micro USB | ×1 | GMC-U6 Type-C USB | ×1 |
| GMC-F3 2.5mm (For Fuji) | ×1 | L-Mount | ×1 |

Tech Specs

Model	GM6S
Screen	5.5" IPS HD Ultra-Bright Touch Screen
Screen Ratio	16:9
Resolution	1920×1080
Contrast Ratio	1000:1
Color Depth	8bit
Visual Angle	160°H/160°V
Brightness	1200nit+10%
Power	9W
Power Supply	DC Input: 7-24V, Φ5.5mm×2.1 Plug DC Output: 7.8+0.3V/1.5A, Φ5.5mm×2.1 Plug Type-C: Power Supply Above 18W Lithium Battery: F550/F750/F970 Lithium Battery, 7.2V
Material	Plastic Frame & Metal Shell
Video Format	480i & 576i@50/60Hz, 480P & 576P@50/60Hz 1280×720P@50/60Hz, 1920×1080i@50/60Hz 1920×1080P@23.98/24/25/29.97/30/50/59/59.94/60Hz 3840×2160P@23.98/24/25/29.97/30Hz 4096×2160P@23.98/24/25/29.97/30Hz
Audio Output	3.5mm Earphone Dual-Channel Output
SD Card Slot	Support Importing Cube Files and Firmware Upgrade by SD Card Support 17/32/33/64/65 Cube
Working Temperature	-10°C~50°C
Dimension	14.5×8.7×2.8cm
Net Weight	273g

What's in the Box



- | | | | |
|-----------------|----|---------------|----|
| Monitor | ×1 | HDMI to Mini | ×1 |
| Hood | ×1 | HDMI to Micro | ×1 |
| Cold Shoe Mount | ×1 | HDMI to HDMI | ×1 |

Optional Purchase



- | | | | |
|-------------------------|----|------------------------|----|
| GMC-S2 Multi | ×1 | GMC-U6 Type-C USB | ×1 |
| GMC-U4 Micro USB | ×1 | L-Mount | ×1 |
| GMC-F3 2.5mm (For Fuji) | ×1 | CMB-01 Hard Carry Case | ×1 |
| GMC-U5 Mini USB | ×1 | | |

Tech Specs

Model	GM7S
Screen	7" IPS HD Ultra-Bright Touch Screen
Screen Ratio	16:10
Resolution	1920×1200
Contrast Ratio	1000:1
Color Depth	8bit
Visual Angle	160°H/160°V
Brightness	1200nit+10%
Power	10W
Power Supply	DC Input: 7-24V, Φ5.5mm×2.1 Plug DC Output: 7.8+0.3V/1.5A, Φ5.5mm×2.1 Plug Type-C: Power Supply Above 18W Lithium Battery: F550/F750/F970 Lithium Battery,
Material	7.2V Plastic Frame & Metal Shell
Video Format	480i & 576i@50/60Hz 480P & 576P@50/60Hz 1280×720P@50/60Hz 1920×1080i@50/60Hz 1920×1080P@23.98/24/25/29.97/3050/59/59.94/60Hz 3840×2160P@23.98/24/25/29.97/30Hz 4096×2160P@23.98/24/25/29.97/30Hz
Audio Output	3.5mm Earphone Dual-Channel Output by SD Card
SD Card Slot	Support 17/32/33/64/65 Cube
Working Temperature	-10~50°C
Dimension	18×12×3.1cm
Net Weight	507g


Godox Photo Equipment Co.,Ltd

Factory Add: 4th Floor of Building 1, 1st to 4 th Floor of Building 2, 4th Floor of Building 3, 1st to 4th Floor of Building 4, Yaochuan Industrial Zone, Tangwei Community, Fuhai Street, Bao'an District, Shenzhen 518103, China

TEL: +86-(0)755-25701197/25726373

FAX: +86-(0)755-25723423

Email: godox@godox.com



godoxglobal



godoxphotoequipment



GODOX Global



godoxofficial

GM55

4K HDMI 5.5" Touchscreen
On-Camera Monitor



5.5" 4K HDMI Output



Rec.709



Camera Control

160

160° Viewing Angle



IPS Touchscreen

What's in the Box



Monitor	×1	Standard HDMI to Micro Cabel(80cm)	×1
Hood	×1	Standard HDMI to Mini Cable(80cm)	×1
Dustless Cloth	×1	Instruction Manual	×1
Cold Shoe Bracket	×1		

Optional Purchase



GMC-S1 Sony Multi-Port	×1	GMC-U3 USB Type-C	×1
GMC-U1 Micro USB	×1	L-Mount	×1
GMC-U2 Mini USB	×1		



Tech Specs

Model	GM55
Screen	5.5" IPS Touch Screen
Screen Ratio	16:9
Resolution	1920×1080
Power	≤7W
Material	PC Plastic
Contrast Ratio	1000:1
Color Depth	8bit
Dimness	410nit±10%
Visual Angle	160°H/160°V
Video Format	480i & 480P@60Hz, 576i@50Hz & 576P@60Hz 1280×720P@50/60Hz, 1920x1080i@50/60Hz 1920×1080P@23.98/24/25/29.97/30/50/59.94/60Hz 3840×2160P@23.98/24/25/29.97/30Hz 4096×2160P@23.98/24Hz
Audio Output	3.5mm Earphone Dual-Channel Output
SD Card Slot	Support to Lead in. Cube Files by SD Card, Support 17/32/33/64/65 Cube
Power Source	Input: DC 7-24v; Output: the Max. Output of Dummy Battery is DC 8V/1.5A
Battery	Compatible with F550/F750/F970 Lithium Battery
Working Temperature	-10°C~50°C
Dimension	154×90.4×34.3mm(with hood)
Net Weight	318g(with hood)

Godox



ON-CAMERA MONITOR